# Safety Data Sheet CEILCOTE #2 HARDENER CLEAR PART B

Bulk Sales Reference No.: NCA003 SDS Revision Date: 01/13/2022 SDS Revision Number: A1-4



## 1. Identification of the preparation and company

### 1.1. Product identifier

Product Identity CEILCOTE #2 HARDENER CLEAR PART B

Bulk Sales Reference No. NCA003

1.2. Relevant identified uses of the substance or mixture and uses advised against Intended Use

See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name International Paint LLC

Manufacturer: Akzo Nobel Coatings International Paint 6001 Antoine Drive Houston, Texas 77091

Emergency

 CHEMTREC
 (800) 424-9300

 International Paint
 (713) 682-1711

 Poison Control Center
 (800) 854-6813

**Customer Service** 

International Paint (800) 589-1267 Fax No. (800) 631-7481

### 2. Hazard identification of the product

# 2.1. Classification of the substance or mixture

Combustible Liquid;H227 Combustible Liquid.

Org. Perox. E;H242 Heating may cause a fire.

Acute Tox. 4;H302 Harmful if swallowed.

Acute Tox. 4;H312 Harmful in contact with skin.

Skin Corr. 1B;H314 Causes severe skin burns and eye damage.

Eye Dam. 1;H318 Causes serious eye damage. STOT SE 3;H335 May cause respiratory irritation.

STOT RE 2;H373 May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 2;H411 Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.











Danger.

H227 Combustible liquid.

H242 Heating may cause a fire.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P234 Keep only in original container.

P235+410 Keep cool. Protect from sunlight.

P260 Do not breathe mist / vapors / spray.

P264 Wash area of contact thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+352 IF ON SKIN: Wash with soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+312 IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P310 Immediately call a POISON CENTER or doctor / physician.

P314 Get Medical advice / attention if you feel unwell.

P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P363 Wash contaminated clothing before reuse.

P370+376 In case of fire: Stop leak if safe to do so.

P391 Collect spillage.

P403+235 Store in a well ventilated place. Keep cool.

P405 Store locked up.

P420 Store away from other materials.

P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating Health: 3 Flammability: 2 Reactivity: 2

## 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Cumene hydroperoxide CAS Number: 0000080-15-9	75 - 100	Org. Perox. E;H242 Acute Tox. 3;H331 Acute Tox. 4;H312 Acute Tox. 4;H302 STOT RE 2;H373 Skin Corr. 1B;H314 Aquatic Chronic 2;H411	[1]
2,2-Dimethylbenzyl alcohol CAS Number: 0000617-94-7	10 - 25		[1]
Cumene CAS Number: 0000098-82-8	1.0 - 10	Flam. Liq. 3;H226 Asp. Tox. 1;H304 STOT SE 3;H335 Aquatic Chronic 2;H411	[1][2]
Acetophenone CAS Number: 0000098-86-2	1.0 - 10	Acute Tox. 4;H302 Eye Irrit. 2;H319	[1][2]

- [1] Substance classified with a health or environmental hazard.
- [2] Substance with a workplace exposure limit.
- [3] PBT-substance or vPvB-substance.

#### 4. First aid measures

#### 4.1. Description of first aid measures

General Remove contaminated clothing and shoes. Get medical attention immediately. Wash

clothing before reuse. Thoroughly clean or destroy contaminated shoes.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention immediately.

Eyes In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

Get medical attention immediately.

Skin In case of contact, immediately flush skin with soap and plenty of water. Get medical

attention immediately.

Ingestion If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT

induce vomiting unless instructed to do so by medical personnel. Never give anything

by mouth to an unconscious person.

## 4.2. Most important symptoms and effects, both acute and delayed

Overview NOTICE: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be

harmful or fatal. Avoid contact with eyes, skin and clothing.

Inhalation Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or

nervous system causing dizziness, headache or nausea.

Eyes Causes severe eye irritation. Avoid contact with eyes.

Skin Causes skin irritation. May be harmful if absorbed through the skin.

Ingestion Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or

drowsiness.

#### 5. Fire-fighting measures

### 5.1. Extinguishing media

SMALL FIRES: Use water. DO NOT use dry chemical or foam. CO2 or Halon may provide limited control. LARGE FIRES: Flood fire area with water from a distance. Move containers from fire area if you can do so without risk. Do not move cargo or vehicle if cargo has been exposed to heat. Cool containers with flooding quantities of water until well after fire is out. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.

#### 5.2. Special hazards arising from the substance or mixture

No data available

## 5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 140

## 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Keep combustibles (wood, paper, oil, clothing, etc.) away from spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Stop leak if you can do so without risk. Use a NON-COMBUSTIBLE material to absorb the product, and transfer to a container for later disposal. LARGE SPILLS: Dike far ahead of liquid spill to contain released material and runoff from fire control. DO NOT GET WATER INSIDE CONTAINERS. Following product recovery, flush area with water.

### 6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

### 6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 10 to 25 meters (30 to 80 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 100 meters (330 feet).

<sup>\*</sup>The full texts of the phrases are shown in Section 16.

## 7. Handling and storage

## 7.1. Precautions for safe handling

Do not get in eyes, on skin or clothing.

## Handling

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discared after each use.

#### In Storage

Keep away from heat, sparks and flame.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

## 7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

## 8. Exposure controls and personal protection

#### 8.1. Control parameters

#### Exposure

CAS No.	Ingredient	Source	Value	
0000080-15-9	Cumene hydroperoxide	OSHA	No Established Limit	
		ACGIH	No Established Limit	
		NIOSH	No Established Limit	
		Supplier	No Established Limit	
		OHSA, CAN	No Established Limit	
		Mexico	No Established Limit	
		Brazil	No Established Limit	
0000098-82-8	Cumene	OSHA	50 ppm TWA; 245 mg/m3 TWA	
		ACGIH	50 ppm TWA	
		NIOSH	50 ppm TWA; 245 mg/m3 TWA900 ppm IDLH (10% LEL)	
		Supplier	No Established Limit	
		OHSA, CAN	50 ppm TWA	
		Mexico	50 ppm TWA VLE-PPT	
		Brazil	39 ppm TWA LT; 190 mg/m3 TWA LT	
0000098-86-2	Acetophenone	OSHA	No Established Limit	
		ACGIH	10 ppm TWA	
		NIOSH	No Established Limit	
		Supplier	No Established Limit	
		OHSA, CAN	10 ppm TWA	
		Mexico	10 ppm TWA VLE-PPT	
		Brazil	No Established Limit	
0000617-94-7	2,2-Dimethylbenzyl alcohol	OSHA	No Established Limit	
		ACGIH	No Established Limit	
		NIOSH	No Established Limit	

S	Supplier	No Established Limit
1-	OHSA, CAN	No Established Limit
N	/lexico	No Established Limit
В	Brazil	No Established Limit

#### Health Data

CAS No.	Ingredient	Source	Value	
0000080-15-9	Cumene hydroperoxide	NIOSH	No Established Limit	
0000098-82-8	Cumene	NIOSH	Eye skin	
0000098-86-2	Acetophenone	NIOSH	No Established Limit	
0000617-94-7	2,2-Dimethylbenzyl alcohol	NIOSH	No Established Limit	

Carcinogen Data

CAS No.	Ingredient	Source	Value	
0000080-15-9	Cumene hydroperoxide	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0000098-82-8	Cumene	OSHA	Select Carcinogen: Yes	
		NTP	Known: No; Suspected: Yes	
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;	
0000098-86-2	Acetophenone	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
			Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0000617-94-7	0000617-94-7 2,2-Dimethylbenzyl alcohol		Select Carcinogen: No	
			Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	

## 8.2. Exposure controls

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.

Eyes

Avoid contact with eyes. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products. When there is a risk of ignition from static electricity, wear antistatic protective clothing and footwear. Any additional personal protective equipment or measures should be selected based on the risk assessment of the task being performed and should be approved by a specialist before handling this product.

Engineering Controls
Other Work Practices

Depending on the site-specific conditions of use, provide adequate ventilation.

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Appearance Coloured Liquid
Odor threshold Not Measured
pH No Established Limit
Melting point / freezing point Not Measured

Initial boiling point and boiling range

No Established Limit (°C) No Established Limit(°F) (boiling range not measured)

Flash Point 77 (°C) 171 (°F)
Evaporation rate (Ether = 1) Not Measured
Flammability (solid, gas) Not Applicable

Upper/lower flammability or explosive

limits

Lower Explosive Limit:

Upper Explosive Limit: No Established Limit

vapor pressure (Pa) Not Measured
Vapor Density Heavier than air

Specific Gravity 1.06

Solubility in Water Not Measured

Partition coefficient n-octanol/water (Log

Kow)

Auto-ignition temperature Not Measured Decomposition temperature Not Measured

Viscosity (cSt)

No Established Limit Not Measured

VOC % Refer to the Technical Data Sheet or label where information is

available.

Not Measured

## 10. Stability and reactivity

#### 10.1. Reactivity

No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

No data available

## 11. Toxicological information

## Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr
Cumene hydroperoxide - (80-15-9)	382.00, Rat - Category: 4	1,520.00, Rabbit - Category: 4	No data available	No data available
2,2-Dimethylbenzyl alcohol - (617-94-7)	No data available	No data available	No data available	No data available
Cumene - (98-82-8)	1,400.00, Rat - Category: 4	10,627.00, Rabbit - Category: NA	No data available	No data available

# NCA003\_A1

Acetophenone - (98-86-2)	815.00, Rat - Category: 4	16,329.00, Rabbit -	No data available	No data available
		Category: NA		

Item	Category	Hazard
Acute Toxicity (mouth)	4	Harmful if swallowed.
Acute Toxicity (skin)	4	Harmful in contact with skin.
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	1B	Causes severe skin burns and eye damage.
Eye damage/irritation	1	Causes serious eye damage.
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	Not Classified	Not Applicable
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	3	May cause respiratory irritation.
Specific target organ systemic Toxicity (repeated exposure)	2	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not Classified	Not Applicable

## 12. Ecological information

## 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

## Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Cumene hydroperoxide - (80-15-9)	3.90, Oncorhynchus mykiss	18.40, Daphnia magna	3.10 (72 hr), Scenedesmus subspicatus
2,2-Dimethylbenzyl alcohol - (617-94-7)	Not Available	Not Available	0.00 ( hr),
Cumene - (98-82-8)	2.70, Oncorhynchus mykiss	10.60, Daphnia magna	2.60 (72 hr), Pseudokirchneriella subcapitata
Acetophenone - (98-86-2)	155.00, Pimephales promelas	Not Available	0.00 (96 hr),

# 12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

## 13. Disposal considerations

## 13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

#### 14. Transport information

14.1. UN number UN3109

14.2. UN proper shipping name ORGANIC PEROXIDE TYPE F LIQUID (CUMYL

**HYDROPEROXIDE 88%)** 

14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation) IMO / IMDG (Ocean Transportation)

Proper Shipping ORGANIC IMDG Proper ORGANIC

Name PEROXIDE TYPE F Shipping Name PEROXIDE TYPE F LIQUID (CUMYL LIQUID (CUMYL

HYDROPEROXIDE HYDROPEROXIDE

88%)

Hazard Class Organic Peroxide IMDG Hazard Class Organic Peroxide

Sub Class Not applicable

UN / NA Number UN3109

Packing Group Not Applicable IMDG Packing Group Not Applicable

CERCLA/DOT RQ 1.33 gal. / 12 lbs. System Reference 211

Code

14.4. Packing group Not Applicable

14.5. Environmental hazards

IMDG Marine Pollutant: Yes ( Cumene hydroperoxide )

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

#### 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA

Inventory.

WHMIS Classification B3 D2B E C

DOT Marine Pollutants (10%):

(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):

(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%):

Acetophenone (5000 lb final RQ; 2270 kg final RQ)

Cumene (5000 lb final RQ; 2270 kg final RQ)

Cumene hydroperoxide (10 lb final RQ; 4.54 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%):

(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%):

Acetophenone

Cumene

Cumene hydroperoxide

Mass RTK Substances (>1%):

Acetophenone

Cumene

Cumene hydroperoxide

Penn RTK Substances (>1%):

Acetophenone

Cumene

Cumene hydroperoxide

Penn Special Hazardous Substances (>.01%):

(No Product Ingredients Listed)

**RCRA Status:** 

(No Product Ingredients Listed)

N.J. RTK Substances (>1%):

Acetophenone

Cumene

Cumene hydroperoxide

N.J. Special Hazardous Substances (>.01%):

Cumene

Cumene hydroperoxide

N.J. Env. Hazardous Substances (>.1%):

Acetophenone

Cumene

Cumene hydroperoxide

Proposition 65 - Carcinogens (>0%):

Cumene

Proposition 65 - Female Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0%):

(No Product Ingredients Listed)

#### 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H226 Flammable liquid and vapor.

H242 Heating may cause a fire.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

**End of Document**