



Safety Data Sheet

Issue Date 08-May-2024

Revision Date 08-May-2024

Revision Number 27

1. IDENTIFICATION

Product identifier

Product Code N-69-00WHA
Product Name HB EPOXOLINEII TNEMEC WHITE

Other means of identification

Common Name SERIES N69/V69, PART A
UN/ID no. 1263
Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address

Tnemec Company, Inc. 123 W. 23rd Avenue, North Kansas City, MO 64116-3094 (816) 474-3400

Distributor

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| | |
|--|-------------|
| Acute toxicity - Oral | Category 4 |
| Acute toxicity - Inhalation (Dusts/Mists) | Category 4 |
| Skin corrosion/irritation | Category 2 |
| Serious eye damage/eye irritation | Category 1 |
| Skin sensitization | Category 1 |
| Germ cell mutagenicity | Category 1B |
| Carcinogenicity | Category 1A |
| Reproductive Toxicity | Category 1B |
| Specific target organ toxicity (single exposure) | Category 3 |
| Specific target organ toxicity (repeated exposure) | Category 1 |
| Flammable Liquids | Category 3 |

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements
Causes skin irritation

Causes serious eye damage
 May cause an allergic skin reaction
 May cause genetic defects
 May cause cancer
 May damage fertility or the unborn child
 May cause respiratory irritation. May cause drowsiness or dizziness
 Causes damage to organs through prolonged or repeated exposure
 Flammable liquid and vapor



Appearance opaque

Physical state liquid

Odor aromatic

Precautionary Statements

Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Use only outdoors or in a well-ventilated area
 Contaminated work clothing should not be allowed out of the workplace
 Do not breathe dust/fume/gas/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Use explosion-proof electrical/ventilating/lighting/.?/equipment
 Keep cool

Response

IF exposed or concerned: Get medical advice/attention
 Specific treatment (see .? on this label)
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a POISON CENTER or doctor/physician
 If skin irritation or rash occurs: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
 Rinse mouth
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

Other information

May cause long lasting harmful effects to aquatic life

Harmful to aquatic life with long lasting effects

Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).

Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs

SEE SAFETY DATA SHEET

Acute Toxicity

15.2829 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical name | CAS No. | Weight-% |
|-------------------------------|------------|-----------|
| BARIUM SULFATE (TOTAL DUST) | 7727-43-7 | 10 - <30% |
| TITANIUM DIOXIDE (TOTAL DUST) | 13463-67-7 | 10 - <30% |
| Trade secret | - | 10 - <30% |
| XYLENE | 1330-20-7 | 1 - <10% |
| BENZYL ALCOHOL | 100-51-6 | 1 - <10% |
| Trade secret | - | 1 - <10% |
| N-BUTANOL (SKIN) | 71-36-3 | 1 - <10% |
| ETHYL BENZENE | 100-41-4 | 1 - <10% |
| ISOPHORONE DIAMINE | 2855-13-2 | 1 - <10% |
| AMORPHOUS SILICA | 7631-86-9 | 1 - <10% |
| CRYSTALLINE SILICA (QUARTZ) | 14808-60-7 | 0.1 - <1% |
| TETRAETHYLENEPENTAMINE | 112-57-2 | 0.1 - <1% |
| P-P'-ISOPROPYLIDENEDIPHENOL | 80-05-7 | 0.1 - <1% |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

| | |
|---|--|
| General advice | If symptoms persist, call a physician. |
| Eye contact | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately. |
| Skin contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician. |
| Inhalation | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. |
| Ingestion | If swallowed, do not induce vomiting. Get medical attention immediately. |
| Self-protection of the first aider | Use personal protective equipment. Avoid contact with eyes, skin and clothing. |

Most important symptoms and effects, both acute and delayed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Aldehydes. Carbon oxides. Hydrocarbons. Oxides of nitrogen.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Do not breathe vapours or spray mist. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not ingest. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Strong oxidizing agents. Acids. Bases. Cleaning solutions such as Chromerge and Aqua Regia.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

| Chemical name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|---|--|--|--------------------------------------|
| BARIUM SULFATE (TOTAL DUST) 7727-43-7 | TWA: 5 mg/m ³ inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica | TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction | |
| TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7 | TWA: 0.2 mg/m ³ nanoscale respirable particulate matter TWA: 2.5 mg/m ³ finescale respirable particulate matter | TWA: 15 mg/m ³ total dust | 5000 mg/m ³ |
| Trade secret | TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter | TWA: 20 mppcf | 1000 mg/m ³ |
| XYLENE 1330-20-7 | TWA: 20 ppm | TWA: 100 ppm TWA: 435 mg/m ³ | |
| N-BUTANOL (SKIN) 71-36-3 | TWA: 20 ppm | TWA: 100 ppm TWA: 300 mg/m ³ | 1400 ppm |
| ETHYL BENZENE 100-41-4 | TWA: 20 ppm | TWA: 100 ppm TWA: 435 mg/m ³ | 800 ppm |
| AMORPHOUS SILICA 7631-86-9 | - | - | 3000 mg/m ³ |
| CRYSTALLINE SILICA (QUARTZ) 14808-60-7 | TWA: 0.025 mg/m ³ respirable particulate matter | TWA: 50 µg/m ³ | 50 mg/m ³ respirable dust |

Appropriate engineering controls

Engineering measures

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|-----------------------|--------------------------|-----------------------|--------------------------|
| Physical state | liquid | Odor | aromatic |
| Appearance | opaque | Odor threshold | No information available |
| Color | No information available | | |

| <u>Property</u> | <u>Values</u> | <u>Remarks</u> |
|--|--------------------------|----------------|
| pH | | |
| Melting point / freezing point | No data available | |
| Boiling point / boiling range | | |
| Flash point | 26° C / 78° F °F | closed cup |
| Evaporation rate | | |
| Flammability (solid, gas) | No data available | |
| Flammability Limit in Air | | |
| Upper flammability limit | 12.3 | |
| Lower flammability limit | 1.5 | |
| Vapor pressure | | |
| Vapor density | | |
| Specific gravity | 1.82981 | g/cm3 |
| Water solubility | Insoluble in cold water | |
| Solubility in other solvents | | |
| Partition coefficient: n-octanol/water | | |
| Autoignition temperature | No data available | |
| Decomposition temperature | No information available | |
| Kinematic viscosity | No information available | |
| Dynamic viscosity | 1100 centipoises | approx |

Other Information

| | |
|--|--------------------------|
| Molecular weight | No information available |
| Density | 15.2606 lbs/gal |
| Volatile organic compounds (VOC) content | 2.62748 lbs/gal |
| Total volatiles weight percent | 17.2174 % |
| Total volatiles volume percent | 36.6993 % |
| Bulk density | No information available |

10. STABILITY AND REACTIVITY**Reactivity**

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Epoxy constituents.

Incompatible materials

Strong oxidizing agents, Acids, Bases, Cleaning solutions such as Chromerge and Aqua Regia

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Oxides of nitrogen. Aldehydes. Hydrocarbons. Carbon oxides.

11. TOXICOLOGICAL INFORMATION**Information on Likely Routes of Exposure****Inhalation**

Harmful if inhaled. Vapors may irritate throat and respiratory system. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.

Eye contact Causes serious eye damage.
Skin contact Irritating to skin. May cause sensitization by skin contact.
Ingestion Harmful if swallowed.

Information on toxicological effects

Symptoms Eye Damage. Harmful if swallowed. Harmful if inhaled. Skin disorders. Skin irritation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin.
Eye damage/irritation Risk of serious damage to eyes.
Chronic Toxicity Avoid repeated exposure. Prolonged exposure may cause chronic effects. Eye Damage. Causes damage to organs through prolonged or repeated exposure. Skin sensitizer. May damage fertility or the unborn child. May cause cancer. May cause genetic defects.
Sensitization May cause sensitization of susceptible persons.
Mutagenicity May cause genetic defects.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical name | ACGIH | IARC | NTP | OSHA |
|---|-------|----------|-------|------|
| TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7 | A3 | Group 2B | - | X |
| Trade secret | | Group 3 | - | |
| XYLENE 1330-20-7 | | Group 3 | - | |
| ETHYL BENZENE 100-41-4 | A3 | Group 2B | - | X |
| AMORPHOUS SILICA 7631-86-9 | | Group 3 | - | |
| CRYSTALLINE SILICA (QUARTZ) 14808-60-7 | A2 | Group 1 | Known | X |

Reproductive effects Suspected of damaging fertility or the unborn child.
STOT - single exposure Eyes, Central Nervous System (CNS), Skin
STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure
Target organ effects blood, Central nervous system, Central Vascular System (CVS), Gastrointestinal tract, Eyes, kidney, liver, respiratory system, Skin.
Aspiration hazard No information available.

Acute Toxicity 15.2829 % of the mixture consists of ingredient(s) of unknown toxicity.
The following values are calculated based on chapter 3.1 of the GHS document

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects

| Chemical name | Toxicity to algae | Toxicity to fish | Toxicity to daphnia |
|---------------------|-------------------|---|--|
| Trade secret | - | LC50: >100 g/L Brachydanio rerio 96 h semi-static | - |
| XYLENE 1330-20-7 | - | LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L | EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h |

| | | | |
|--|--|---|--|
| | | Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h | |
| BENZYL ALCOHOL 100-51-6 | - | LC50: 460 mg/L Pimephales promelas 96 h static LC50: 10 mg/L Lepomis macrochirus 96 h static | EC50: 23 mg/L water flea 48 h |
| N-BUTANOL (SKIN) 71-36-3 | EC50: >500 mg/L Desmodesmus subspicatus 96 h EC50: >500 mg/L Desmodesmus subspicatus 72 h | LC50: 1730 - 1910 mg/L Pimephales promelas 96 h static LC50: 1740 mg/L Pimephales promelas 96 h flow-through LC50: 100000 - 500000 µg/L Lepomis macrochirus 96 h static LC50: 1910000 µg/L Pimephales promelas 96 h static | EC50: 1983 mg/L Daphnia magna 48 h EC50: 1897 - 2072 mg/L Daphnia magna 48 h Static |
| ETHYL BENZENE 100-41-4 | EC50: 4.6 mg/L Pseudokirchneriella subcapitata 72 h EC50: >438 mg/L Pseudokirchneriella subcapitata 96 h EC50: 2.6 - 11.3 mg/L Pseudokirchneriella subcapitata 72 h static EC50: 1.7 - 7.6 mg/L Pseudokirchneriella subcapitata 96 h static | LC50: 11.0 - 18.0 mg/L Oncorhynchus mykiss 96 h static LC50: 4.2 mg/L Oncorhynchus mykiss 96 h semi-static LC50: 7.55 - 11 mg/L Pimephales promelas 96 h flow-through LC50: 32 mg/L Lepomis macrochirus 96 h static LC50: 9.1 - 15.6 mg/L Pimephales promelas 96 h static LC50: 9.6 mg/L Poecilia reticulata 96 h static | EC50: 1.8 - 2.4 mg/L Daphnia magna 48 h |
| ISOPHORONE DIAMINE 2855-13-2 | EC50: 37 mg/L Desmodesmus subspicatus 72 h | - | EC50: 14.6 - 21.5 mg/L Daphnia magna 48 h semi-static |
| AMORPHOUS SILICA 7631-86-9 | EC50: 440 mg/L Pseudokirchneriella subcapitata 72 h | LC50: 5000 mg/L Brachydanio rerio 96 h static | EC50: 7600 mg/L Ceriodaphnia dubia 48 h |
| TETRAETHYLENEPENTAMINE 112-57-2 | EC50: 2.1 mg/L Pseudokirchneriella subcapitata 72 h | LC50: 420 mg/L Poecilia reticulata 96 h static | EC50: 24.1 mg/L Daphnia magna 48 h |
| P-P'-ISOPROPYLIDENEDIPHENOL 80-05-7 | EC50: 2.5 mg/L Pseudokirchneriella subcapitata 96 h | LC50: 3.6 - 5.4 mg/L Pimephales promelas 96 h flow-through LC50: 4.0 - 5.5 mg/L Pimephales promelas 96 h static LC50: 4 mg/L Oncorhynchus mykiss 96 h LC50: 9.9 mg/L Brachydanio rerio 96 h static | EC50: 10.2 mg/L Daphnia magna 48 h EC50: 3.9 mg/L Daphnia magna 48 h EC50: 9.2 - 11.4 mg/L Daphnia magna 48 h Static |

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

| Chemical name | log Pow |
|---------------------------------|--------------|
| XYLENE 1330-20-7 | 2.77 |
| BENZYL ALCOHOL 100-51-6 | 1.05 |
| N-BUTANOL (SKIN) 71-36-3 | 0.785 |
| ETHYL BENZENE 100-41-4 | 3.118 |
| ISOPHORONE DIAMINE 2855-13-2 | 0.99 2.33 |

| | |
|--|-----|
| TETRAETHYLENEPENTAMINE 112-57-2 | .99 |
| P-P'-ISOPROPYLIDENEDIPHENOL 80-05-7 | 3.4 |

Other Adverse Effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal Methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

US EPA Waste Number

| Chemical name | RCRA | RCRA - Basis for Listing | RCRA - D Series Wastes | RCRA - U Series Wastes |
|-----------------------------|------|---|------------------------|------------------------|
| XYLENE 1330-20-7 | | Included in waste stream: F039 | | U239 |
| N-BUTANOL (SKIN) 71-36-3 | | Included in waste stream: F039 | | U031 |
| ETHYL BENZENE 100-41-4 | | Included in waste stream: F039 | | |
| FORMALDEHYDE 50-00-0 | U122 | Included in waste streams: K009, K010, K038, K040, K156, K157 | | U122 |

California Hazardous Waste Status

| Chemical name | CAWAST |
|-----------------------------|--------------------|
| XYLENE 1330-20-7 | Toxic Ignitable |
| N-BUTANOL (SKIN) 71-36-3 | Toxic |
| ETHYL BENZENE 100-41-4 | Toxic Ignitable |

14. TRANSPORT INFORMATION

DOT

UNID no. 1263
 Proper Shipping Name PAINT
 Hazard Class 3
 Packing Group III
 Emergency Response Guide Number 128

Additional Information Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

| | |
|----------------------|-----------------|
| TSCA | Complies |
| DSL/NDSL | Complies |
| EINECS/ELINCS | Complies |
| ENCS | Does Not Comply |
| IECSC | Complies |
| KECL | Does Not Comply |
| PICCS | Does Not Comply |
| AICS | Does Not Comply |

- TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
- ENCS** - Japan Existing and New Chemical Substances
- IECSC** - China Inventory of Existing Chemical Substances
- KECL** - Korean Existing and Evaluated Chemical Substances
- PICCS** - Philippines Inventory of Chemicals and Chemical Substances
- AICS** - Australian Inventory of Chemical Substances

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

| | |
|----------------------|------------------|
| Chemical name | HAPS Data |
| XYLENE | |
| ETHYL BENZENE | |

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

| Chemical name | SARA 313 - Threshold Values |
|---|-----------------------------|
| BARIUM SULFATE (TOTAL DUST) - 7727-43-7 | 1.0 |
| XYLENE - 1330-20-7 | 1.0 |
| N-BUTANOL (SKIN) - 71-36-3 | 1.0 |
| ETHYL BENZENE - 100-41-4 | 0.1 |
| P-P'-ISOPROPYLIDENEDIPHENOL - 80-05-7 | 1.0 |

SARA 311/312 Hazardous

Categorization

| | |
|--|-----|
| Acute Health Hazard | Yes |
| Chronic Health Hazard | Yes |
| Fire Hazard | Yes |
| Sudden Release of Pressure Hazard | No |
| Reactive Hazard | No |

Clean Water Act

| Chemical name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---------------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| XYLENE 1330-20-7 | 100 lb | | | X |
| ETHYL BENZENE 100-41-4 | 1000 lb | X | X | X |

CERCLA

| Chemical name | Hazardous Substances RQs | CERCLA EHS RQs | RQ |
|-----------------------------|--------------------------|----------------|--|
| XYLENE 1330-20-7 | 100 lb | | RQ 100 lb final RQ RQ 45.4 kg final RQ |
| N-BUTANOL (SKIN) 71-36-3 | 5000 lb | | RQ 5000 lb final RQ RQ 2270 kg final RQ |
| ETHYL BENZENE | 1000 lb | | RQ 1000 lb final RQ |

| | | | |
|----------|--|--|--------------------|
| 100-41-4 | | | RQ 454 kg final RQ |
|----------|--|--|--------------------|

California Prop. 65

WARNING: This product can expose you to the following chemicals which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

| Chemical name | California Prop. 65 |
|--|--------------------------------------|
| TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7 | Carcinogen |
| ETHYL BENZENE - 100-41-4 | Carcinogen |
| CRYSTALLINE SILICA (QUARTZ) - 14808-60-7 | Carcinogen |
| P-P'-ISOPROPYLIDENEDIPHENOL - 80-05-7 | Developmental Female Reproductive |
| FORMALDEHYDE - 50-00-0 | Carcinogen |

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

| Chemical name | New Jersey | Massachusetts | Pennsylvania |
|---|------------|---------------|--------------|
| BARIUM SULFATE (TOTAL DUST) 7727-43-7 | X | X | X |
| TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7 | X | X | X |
| Trade secret | X | X | X |
| XYLENE 1330-20-7 | X | X | X |
| BENZYL ALCOHOL 100-51-6 | | X | X |
| N-BUTANOL (SKIN) 71-36-3 | X | X | X |
| ETHYL BENZENE 100-41-4 | X | X | X |
| ISOPHORONE DIAMINE 2855-13-2 | X | | |
| AMORPHOUS SILICA 7631-86-9 | | X | X |
| CRYSTALLINE SILICA (QUARTZ) 14808-60-7 | X | X | X |
| TETRAETHYLENEPENTAMINE 112-57-2 | X | X | X |
| P-P'-ISOPROPYLIDENEDIPHENOL 80-05-7 | X | X | X |

16. OTHER INFORMATION

| | | | | |
|---|-----------|----------------|---------------|-------------------|
| NFPA | Health 2 | Flammability 3 | Instability 1 | Physical hazard * |
| HMIS (Hazardous Material Information System) | Health 2* | Flammability 3 | Reactivity 1 | |

Prepared By Tnemec Regulatory Dept: 816-474-3400
Issue Date 23-May-2017
Revision Date 08-May-2024
Revision Summary
 9 4 5 7 10 8 2 11 14 1 13 15


Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal

Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS



Safety Data Sheet

Issue Date 02-Jul-2024

Revision Date 08-May-2024

Revision Number 43

1. IDENTIFICATION

Product identifier

Product Code N-69-0069B
Product Name H-B EPOXOLINE II CONVERTER

Other means of identification

Common Name SERIES N69/N69F, PART B
UN/ID no. UN1263
Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address

Tnemec Company, Inc. 123 W. 23rd Avenue, North Kansas City, MO 64116-3094 (816) 474-3400

Distributor

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)
Emergency Telephone 800-535-5053 (INFOTRAC) - TNE MEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| | |
|--|-------------|
| Acute toxicity - Oral | Category 4 |
| Acute toxicity - Inhalation (Vapors) | Category 4 |
| Acute toxicity - Inhalation (Dusts/Mists) | Category 4 |
| Skin corrosion/irritation | Category 2 |
| Serious eye damage/eye irritation | Category 2 |
| Skin sensitization | Category 1 |
| Germ cell mutagenicity | Category 1B |
| Carcinogenicity | Category 1A |
| Reproductive Toxicity | Category 2 |
| Specific target organ toxicity (repeated exposure) | Category 2 |

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes skin irritation
 Causes serious eye irritation
 May cause an allergic skin reaction
 May cause genetic defects
 May cause cancer
 Suspected of damaging fertility or the unborn child
 May cause damage to organs through prolonged or repeated exposure



Appearance opaque

Physical state liquid

Odor aromatic

Precautionary Statements

Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Use only outdoors or in a well-ventilated area
 Contaminated work clothing should not be allowed out of the workplace
 Do not breathe dust/fume/gas/mist/vapors/spray

Response

IF exposed or concerned: Get medical advice/attention
 specific treatment
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN: Wash with plenty of soap and water
 Take off contaminated clothing and wash before reuse
 If skin irritation or rash occurs: Get medical advice/attention
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
 Rinse mouth

Storage

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

May be harmful in contact with skin
 Toxic to aquatic life with long lasting effects
 Acute Toxicity 42.5272 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical name | CAS No. | Weight-% |
|--------------------|------------|-----------|
| MAGNESIUM SILICATE | 14807-96-6 | 30 - <60% |

| | | |
|------------------------------|------------|-----------|
| EPOXY RESIN (LER) | 25085-99-8 | 10 - <30% |
| SOLID EPOXY RESIN | - | 10 - <30% |
| BARIUM SULFATE (TOTAL DUST) | 7727-43-7 | 1 - <10% |
| XYLENE | 1330-20-7 | 1 - <10% |
| METHYL ISOBUTYL KETONE | 108-10-1 | 1 - <10% |
| AROMATIC HYDROCARBON MIXTURE | 64742-95-6 | 1 - <10% |
| XYLENE | 1330-20-7 | 1 - <10% |
| ETHYL BENZENE | 100-41-4 | 1 - <10% |
| TOLUENE | 108-88-3 | 0.1 - <1% |
| CUMENE (SKIN) | 98-82-8 | 0.1 - <1% |
| CRYSTALLINE SILICA (QUARTZ) | 14808-60-7 | 0.1 - <1% |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

| | |
|---|--|
| General advice | If symptoms persist, call a physician. |
| Eye contact | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist. |
| Skin contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician. |
| Inhalation | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. |
| Ingestion | If swallowed, do not induce vomiting. Get medical attention immediately. |
| Self-protection of the first aider | Use personal protective equipment. Avoid contact with eyes, skin and clothing. |

Most important symptoms and effects, both acute and delayed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Aldehydes. Chlorine. Fluorine.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapours or spray mist. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not ingest. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Acids. Bases. Amines. Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

| Chemical name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|--|--|--|------------------------|
| MAGNESIUM SILICATE 14807-96-6 | TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter | TWA: 20 mppcf | 1000 mg/m ³ |
| BARIUM SULFATE (TOTAL DUST) 7727-43-7 | TWA: 5 mg/m ³ inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica | TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction | |
| XYLENE 1330-20-7 | TWA: 20 ppm | TWA: 100 ppm TWA: 435 mg/m ³ | |
| METHYL ISOBUTYL KETONE 108-10-1 | TWA: 20 ppm STEL: 75 ppm | TWA: 100 ppm TWA: 410 mg/m ³ | 500 ppm |
| XYLENE 1330-20-7 | TWA: 20 ppm | TWA: 100 ppm TWA: 435 mg/m ³ | |

| | | | |
|---|---|---|--------------------------------------|
| ETHYL BENZENE 100-41-4 | TWA: 20 ppm | TWA: 100 ppm TWA: 435 mg/m ³ | 800 ppm |
| TOLUENE 108-88-3 | TWA: 20 ppm | TWA: 200 ppm Ceiling: 300 ppm | 500 ppm |
| CUMENE (SKIN) 98-82-8 | TWA: 5 ppm | TWA: 50 ppm TWA: 245 mg/m ³ Skin | 900 ppm |
| CRYSTALLINE SILICA (QUARTZ) 14808-60-7 | TWA: 0.025 mg/m ³ respirable particulate matter | TWA: 50 µg/m ³ | 50 mg/m ³ respirable dust |

Appropriate engineering controls**Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

Skin and body protection

Wear protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|---|--------------------------|-----------------------------|--------------------------|
| Physical state | liquid | Odor | aromatic |
| Appearance | opaque | Odor threshold | No information available |
| Color | No information available | | |
| Property | Values | Remarks | |
| pH | | No data available | |
| Melting point / freezing point | No data available | No data available | |
| Boiling point / boiling range | | No information available | |
| Flash point | 35° C / 95° F | Pensky Martens - Closed Cup | |
| Evaporation rate | | No data available | |
| Flammability (solid, gas) | No data available | No information available | |
| Flammability Limit in Air | | | |
| Upper flammability limit | 12.3 | | |
| Lower flammability limit | 0.9 | | |
| Vapor pressure | | No data available | |
| Vapor density | | No data available | |
| Specific gravity | 1.44716 | g/cm ³ | |
| Water solubility | Insoluble in cold water | | |
| Solubility in other solvents | | No data available | |
| Partition coefficient: n-octanol/water | | No data available | |
| Autoignition temperature | No data available | No data available | |
| Decomposition temperature | No information available | No data available | |
| Kinematic viscosity | No information available | No data available | |

Dynamic viscosity No data available

Other Information

Molecular weight No information available
Density 12.06933
Volatile organic compounds (VOC) content 2.11925
Total volatiles weight percent 17.559 %
Total volatiles volume percent 29.8587 %
Bulk density No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Acids, Bases, Amines, Strong oxidizing agents

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Aldehydes. Chlorine. Fluorine.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

| | |
|---------------------|--|
| Inhalation | Harmful if inhaled. May cause drowsiness or dizziness. May cause irritation. |
| Eye contact | Causes serious eye irritation. |
| Skin contact | Irritating to skin. May cause sensitization by skin contact. |
| Ingestion | Harmful if swallowed. |

Information on toxicological effects

Symptoms Harmful if swallowed. Harmful if inhaled. Skin disorders. Irritating to eyes and skin. May cause respiratory irritation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| | |
|----------------------------------|--|
| Skin corrosion/irritation | Irritating to skin. sensitizer. |
| Eye damage/irritation | Irritating to eyes. |
| Chronic Toxicity | Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause genetic defects. May cause cancer. May cause an allergic skin reaction. Causes damage to organs through prolonged or repeated exposure. |
| Sensitization | May cause sensitization of susceptible persons. |

Mutagenicity May cause genetic defects.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical name | ACGIH | IARC | NTP | OSHA |
|--|-------|----------|------------------------|------|
| MAGNESIUM SILICATE 14807-96-6 | | Group 3 | - | |
| XYLENE 1330-20-7 | | Group 3 | - | |
| METHYL ISOBUTYL KETONE 108-10-1 | A3 | Group 2B | - | X |
| XYLENE 1330-20-7 | | Group 3 | - | |
| ETHYL BENZENE 100-41-4 | A3 | Group 2B | - | X |
| TOLUENE 108-88-3 | | Group 3 | - | |
| CUMENE (SKIN) 98-82-8 | A3 | Group 2B | Reasonably Anticipated | X |
| CRYSTALLINE SILICA (QUARTZ) 14808-60-7 | A2 | Group 1 | Known | X |

Reproductive effects No information available.
STOT - single exposure Causes damage to organs
STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure
Aspiration hazard No information available.

Acute Toxicity 42.5272 % of the mixture consists of ingredient(s) of unknown toxicity.
The following values are calculated based on chapter 3.1 of the GHS document

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects

| Chemical name | Toxicity to algae | Toxicity to fish | Toxicity to daphnia |
|--|---|---|--|
| MAGNESIUM SILICATE 14807-96-6 | - | LC50: >100 g/L Brachydanio rerio 96 h semi-static | - |
| EPOXY RESIN (LER) 25085-99-8 | 11 mg/L 72 hr | 2 mg/L 96 hr Oncorhynchus mykiss | 1.8 mg/L 48h |
| XYLENE 1330-20-7 | - | LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h | EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h |
| METHYL ISOBUTYL KETONE 108-10-1 | EC50: 400 mg/L Pseudokirchneriella subcapitata 96 h | LC50: 496 - 514 mg/L Pimephales promelas 96 h flow-through | EC50: 170 mg/L Daphnia magna 48 h |
| AROMATIC HYDROCARBON MIXTURE 64742-95-6 | - | LC50: 9.22 mg/L Oncorhynchus mykiss 96 h | EC50: 6.14 mg/L Daphnia magna 48 h |
| XYLENE 1330-20-7 | - | LC50: 13.4 mg/L Pimephales promelas 96 h flow-through LC50: 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h static | EC50: 3.82 mg/L water flea 48 h LC50: 0.6 mg/L Gammarus lacustris 48 h |

| | | | |
|--|--|---|---|
| | | <p>LC50: 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50: 13.1 - 16.5 mg/L Lepomis macrochirus 96 h flow-through LC50: 19 mg/L Lepomis macrochirus 96 h LC50: 7.711 - 9.591 mg/L Lepomis macrochirus 96 h static LC50: 23.53 - 29.97 mg/L Pimephales promelas 96 h static LC50: 780 mg/L Cyprinus carpio 96 h semi-static LC50: >780 mg/L Cyprinus carpio 96 h LC50: 30.26 - 40.75 mg/L Poecilia reticulata 96 h static</p> | |
| <p>ETHYL BENZENE 100-41-4</p> | <p>EC50: 4.6 mg/L Pseudokirchneriella subcapitata 72 h EC50: >438 mg/L Pseudokirchneriella subcapitata 96 h EC50: 2.6 - 11.3 mg/L Pseudokirchneriella subcapitata 72 h static EC50: 1.7 - 7.6 mg/L Pseudokirchneriella subcapitata 96 h static</p> | <p>LC50: 11.0 - 18.0 mg/L Oncorhynchus mykiss 96 h static LC50: 4.2 mg/L Oncorhynchus mykiss 96 h semi-static LC50: 7.55 - 11 mg/L Pimephales promelas 96 h flow-through LC50: 32 mg/L Lepomis macrochirus 96 h static LC50: 9.1 - 15.6 mg/L Pimephales promelas 96 h static LC50: 9.6 mg/L Poecilia reticulata 96 h static</p> | <p>EC50: 1.8 - 2.4 mg/L Daphnia magna 48 h</p> |
| <p>TOLUENE 108-88-3</p> | <p>EC50: >433 mg/L Pseudokirchneriella subcapitata 96 h EC50: 12.5 mg/L Pseudokirchneriella subcapitata 72 h static</p> | <p>LC50: 15.22 - 19.05 mg/L Pimephales promelas 96 h flow-through LC50: 12.6 mg/L Pimephales promelas 96 h static LC50: 5.89 - 7.81 mg/L Oncorhynchus mykiss 96 h flow-through LC50: 14.1 - 17.16 mg/L Oncorhynchus mykiss 96 h static LC50: 5.8 mg/L Oncorhynchus mykiss 96 h semi-static LC50: 11.0 - 15.0 mg/L Lepomis macrochirus 96 h static LC50: 54 mg/L Oryzias latipes 96 h static LC50: 28.2 mg/L Poecilia reticulata 96 h semi-static LC50: 50.87 - 70.34 mg/L Poecilia reticulata 96 h static</p> | <p>EC50: 5.46 - 9.83 mg/L Daphnia magna 48 h Static EC50: 11.5 mg/L Daphnia magna 48 h</p> |
| <p>CUMENE (SKIN) 98-82-8</p> | <p>EC50: 2.6 mg/L Pseudokirchneriella subcapitata 72 h</p> | <p>LC50: 6.04 - 6.61 mg/L Pimephales promelas 96 h flow-through LC50: 4.8 mg/L Oncorhynchus mykiss 96 h flow-through LC50: 2.7 mg/L Oncorhynchus mykiss 96 h semi-static LC50: 5.1 mg/L Poecilia reticulata 96 h semi-static</p> | <p>EC50: 0.6 mg/L Daphnia magna 48 h EC50: 7.9 - 14.1 mg/L Daphnia magna 48 h Static</p> |

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

| Chemical name | log Pow |
|-------------------|---------|
| EPOXY RESIN (LER) | 3 |

| | |
|------------------------------------|----------------------|
| 25085-99-8 | |
| XYLENE 1330-20-7 | 2.77 |
| METHYL ISOBUTYL KETONE 108-10-1 | 1.19 |
| XYLENE 1330-20-7 | 2.77 - 3.15 |
| ETHYL BENZENE 100-41-4 | 3.118 |
| TOLUENE 108-88-3 | 2.73 3.44 3.93 |
| CUMENE (SKIN) 98-82-8 | 3.55 |

Other Adverse Effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal Methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

US EPA Waste Number

| Chemical name | RCRA | RCRA - Basis for Listing | RCRA - D Series Wastes | RCRA - U Series Wastes |
|------------------------------------|------|--|---------------------------|------------------------|
| XYLENE 1330-20-7 | | Included in waste stream: F039 | | U239 |
| METHYL ISOBUTYL KETONE 108-10-1 | | Included in waste stream: F039 | | U161 |
| XYLENE 1330-20-7 | | Included in waste stream: F039 | | U239 |
| ETHYL BENZENE 100-41-4 | | Included in waste stream: F039 | | |
| TOLUENE 108-88-3 | U220 | Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151 | | U220 |
| CUMENE (SKIN) 98-82-8 | | | | U055 |
| BENZENE 71-43-2 | U019 | Included in waste streams: F005, F024, F025, F037, F038, F039, K085, K104, K105, K141, K142, K143, K144, K145, K147, K151, K159, K169, K171, K172 | 0.5 mg/L regulatory level | U019 |

| Chemical name | RCRA - Halogenated Organic Compounds | RCRA - P Series Wastes | RCRA - F Series Wastes | RCRA - K Series Wastes |
|---------------------|--------------------------------------|------------------------|--|------------------------|
| TOLUENE 108-88-3 | | | Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic | |

| | | | | |
|--|--|--|--|--|
| | | | hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution. | |
|--|--|--|--|--|

California Hazardous Waste Status

| Chemical name | CAWAST |
|---------------------------|--------------------|
| XYLENE 1330-20-7 | Toxic Ignitable |
| XYLENE 1330-20-7 | Toxic Ignitable |
| ETHYL BENZENE 100-41-4 | Toxic Ignitable |
| TOLUENE 108-88-3 | Toxic Ignitable |
| CUMENE (SKIN) 98-82-8 | Toxic Ignitable |

14. TRANSPORT INFORMATION

DOT

UN/ID no. UN1263
Proper Shipping Name PAINT
Hazard Class 3
Packing Group III
Emergency Response Guide Number 128
Additional Information The above transport information is for non-bulk packaging only (≤ 119 gallons). For additional information, contact Tnemec Traffic Department at 816-474-3400 or traffic@tnemec.com.

IATA

UN/ID no. UN1263
Proper Shipping Name PAINT, (Epoxy Resin)
Hazard Class 3
Packing Group III
ERG Code 128

IMDG/IMO

UN/ID no. UN1263
Proper Shipping Name PAINT, (Epoxy Resin)
Hazard Class 3
Packing Group III
EmS No. F-E,S-E
Marine Pollutant Yes

Additional Information Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies

| | |
|----------------------|-----------------|
| EINECS/ELINCS | Does Not Comply |
| ENCS | Does Not Comply |
| IECSC | Complies |
| KECL | Complies |
| PICCS | Complies |
| AICS | Does Not Comply |

- TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
- ENCS** - Japan Existing and New Chemical Substances
- IECSC** - China Inventory of Existing Chemical Substances
- KECL** - Korean Existing and Evaluated Chemical Substances
- PICCS** - Philippines Inventory of Chemicals and Chemical Substances
- AICS** - Australian Inventory of Chemical Substances

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

| Chemical name | HAPS Data |
|------------------------|-----------|
| XYLENE | |
| METHYL ISOBUTYL KETONE | |
| XYLENE | |
| ETHYL BENZENE | |
| TOLUENE | |
| CUMENE (SKIN) | |

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

| Chemical name | SARA 313 - Threshold Values |
|---|-----------------------------|
| BARIUM SULFATE (TOTAL DUST) - 7727-43-7 | 1.0 |
| XYLENE - 1330-20-7 | 1.0 |
| METHYL ISOBUTYL KETONE - 108-10-1 | 0.1 |
| XYLENE - 1330-20-7 | 1.0 |
| ETHYL BENZENE - 100-41-4 | 0.1 |
| TOLUENE - 108-88-3 | 1.0 |
| CUMENE (SKIN) - 98-82-8 | 0.1 |

SARA 311/312 Hazardous

Categorization

| | |
|--|-----|
| Acute Health Hazard | Yes |
| Chronic Health Hazard | Yes |
| Fire Hazard | Yes |
| Sudden Release of Pressure Hazard | No |
| Reactive Hazard | No |

Clean Water Act

| Chemical name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---------------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| XYLENE 1330-20-7 | 100 lb | | | X |
| XYLENE 1330-20-7 | 100 lb | | | X |
| ETHYL BENZENE 100-41-4 | 1000 lb | X | X | X |
| TOLUENE 108-88-3 | 1000 lb | X | X | X |

CERCLA

| Chemical name | Hazardous Substances RQs | CERCLA EHS RQs | RQ |
|------------------------------------|--------------------------|----------------|---|
| XYLENE 1330-20-7 | 100 lb | | RQ 100 lb final RQ RQ 45.4 kg final RQ |
| METHYL ISOBUTYL KETONE 108-10-1 | 5000 lb | | RQ 5000 lb final RQ RQ 2270 kg final RQ |
| XYLENE 1330-20-7 | 100 lb | | RQ 100 lb final RQ RQ 45.4 kg final RQ |
| ETHYL BENZENE 100-41-4 | 1000 lb | | RQ 1000 lb final RQ RQ 454 kg final RQ |
| TOLUENE 108-88-3 | 1000 lb 1 lb | | RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ |
| CUMENE (SKIN) 98-82-8 | 5000 lb | | RQ 5000 lb final RQ RQ 2270 kg final RQ |

California Prop. 65

WARNING: This product can expose you to the following chemicals which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

| Chemical name | California Prop. 65 |
|--|--|
| METHYL ISOBUTYL KETONE - 108-10-1 | Carcinogen Developmental |
| ETHYL BENZENE - 100-41-4 | Carcinogen |
| TOLUENE - 108-88-3 | Developmental |
| CUMENE (SKIN) - 98-82-8 | Carcinogen |
| CRYSTALLINE SILICA (QUARTZ) - 14808-60-7 | Carcinogen |
| BENZENE - 71-43-2 | Carcinogen Developmental Male Reproductive |

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

| Chemical name | New Jersey | Massachusetts | Pennsylvania |
|---|------------|---------------|--------------|
| MAGNESIUM SILICATE 14807-96-6 | X | X | X |
| BARIUM SULFATE (TOTAL DUST) 7727-43-7 | X | X | X |
| XYLENE 1330-20-7 | X | X | X |
| METHYL ISOBUTYL KETONE 108-10-1 | X | X | X |
| XYLENE 1330-20-7 | X | X | X |
| ETHYL BENZENE 100-41-4 | X | X | X |
| TOLUENE 108-88-3 | X | X | X |
| CUMENE (SKIN) 98-82-8 | X | X | X |
| CRYSTALLINE SILICA (QUARTZ) 14808-60-7 | X | X | X |

16. OTHER INFORMATION

NFPA Health 2 Flammability 3 Instability 1 Physical hazard *
HMIS (Hazardous) Health 2* Flammability 3 Reactivity 1

**Material Information
System)**

Prepared By Tnemec Regulatory Dept: 816-474-3400
Revision Date 08-May-2024
Revision Summary
9 4 5 7 10 8 11 14 15 13

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910. To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS