



# Safety Data Sheet

Issue Date 30-Jan-2024

Revision Date 30-Jan-2024

Revision Number 12

## 1. IDENTIFICATION

### Product identifier

**Product Code** S282-11WHA  
**Product Name** TNEME-GLAZE WHITE

### Other means of identification

**Common Name** SERIES 282, PART A  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 123 W. 23rd Avenue, North Kansas City, MO 64116-3094 (816) 474-3400

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

|  |             |
|--|-------------|
| Acute toxicity - Inhalation (Vapors)               | Category 4  |
| Skin corrosion/irritation                          | Category 2  |
| Serious eye damage/eye irritation                  | Category 1  |
| Skin sensitization                                 | Category 1A |
| Germ cell mutagenicity                             | Category 1B |
| Carcinogenicity                                    | Category 1A |
| Reproductive Toxicity                              | Category 2  |
| Specific target organ toxicity (single exposure)   | Category 2  |
| Specific target organ toxicity (repeated exposure) | Category 1  |

### Label elements

## EMERGENCY OVERVIEW

#### **Danger**

#### **Hazard statements**

Harmful if inhaled  
Causes skin irritation  
Causes serious eye damage  
May cause an allergic skin reaction

May cause genetic defects  
 May cause cancer  
 Suspected of damaging fertility or the unborn child  
 May cause damage to organs  
 Causes damage to organs through prolonged or repeated exposure  
 May be corrosive to metals



**Appearance** opaque

**Physical state** liquid

**Odor** Slight

### Precautionary Statements

#### Prevention

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Use only outdoors or in a well-ventilated area  
 Wash face, hands and any exposed skin thoroughly after handling  
 Contaminated work clothing should not be allowed out of the workplace  
 Wear protective gloves  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Do not eat, drink or smoke when using this product

#### Response

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Immediately call a POISON CENTER or doctor/physician  
 IF ON SKIN: Wash with plenty of soap and water  
 Take off contaminated clothing and wash before reuse  
 If skin irritation or rash occurs: Get medical advice/attention  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

#### Storage

Store locked up  
 Keep away from children

#### Disposal

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

#### Other information

Toxic to aquatic life with long lasting effects  
 SEE SAFETY DATA SHEET  
 Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).  
 Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs  
 Acute Toxicity 24.2484018 % of the mixture consists of ingredient(s) of unknown toxicity.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical name               | CAS No.    | Weight-%  |
|-----------------------------|------------|-----------|
| CRYSTALLINE SILICA (QUARTZ) | 14808-60-7 | 30 - <60% |

|                                      |             |           |
|--------------------------------------|-------------|-----------|
| BENZYL ALCOHOL                       | 100-51-6    | 10 - <30% |
| SILICON DIOXIDE/ALUMINUM OXIDES      | 66402-68-4  | 10 - <30% |
| TITANIUM DIOXIDE (TOTAL DUST)        | 13463-67-7  | 1 - <10%  |
| MODIFIED ALIPHATIC AMINE             | -           | 1 - <10%  |
| POLYOXYPROPYLENETRIAMINE             | 39423-51-3  | 1 - <10%  |
| MODIFIED CYCLOALIPHATIC POLYAMINE    | 1761-71-3   | 1 - <10%  |
| MODIFIED CYCLOALIPHATIC AMINE ADDUCT | 129733-57-9 | 1 - <10%  |
| NONYLPHENOL                          | 84852-15-3  | 1 - <10%  |
| STODDARD SOLVENT (MINERAL SPIRITS)   | 8052-41-3   | 0.1 - <1% |

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

|   |  |
|---|--|
| <b>General advice</b>                     | If symptoms persist, call a physician.   |
| <b>Eye contact</b>                        | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately.                               |
| <b>Skin contact</b>                       | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. |
| <b>Inhalation</b>                         | Remove to fresh air. Oxygen or artificial respiration if needed.   |
| <b>Ingestion</b>                          | If swallowed, do not induce vomiting. Get medical attention immediately.   |
| <b>Self-protection of the first aider</b> | Use personal protective equipment. Avoid contact with eyes, skin and clothing.   |

##### Most important symptoms and effects, both acute and delayed

|                           |                        |
|---------------------------|------------------------|
| <b>Notes to physician</b> | Treat symptomatically. |
|---------------------------|------------------------|

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Aldehydes. Carbon oxides. Hydrocarbons. Oxides of nitrogen. Ammonia. Phenolics. Nitric acid, nitrosamine. Ketones.

##### Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation.

#### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

#### Methods and material for containment and cleaning up

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

#### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents. Acids. Bases. Hypochlorites. Nitrous acid and other nitrosating agents. Peroxides.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

#### Exposure guidelines

| Chemical name                                   | ACGIH TLV  | OSHA PEL                                    | NIOSH IDLH                                    |
|---|--|---|---|
| CRYSTALLINE SILICA (QUARTZ)<br>14808-60-7       | TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter   | TWA: 50 µg/m <sup>3</sup>                   | 50 mg/m <sup>3</sup> respirable dust          |
| SILICON DIOXIDE/ALUMINUM OXIDES<br>66402-68-4   | TWA: 5 mg/m <sup>3</sup><br>TWA: 0.02 mg/m <sup>3</sup> respirable particulate matter<br>TWA: 0.1 mg/m <sup>3</sup> inhalable particulate matter | Ceiling: 5 mg/m <sup>3</sup>                | 500 mg/m <sup>3</sup><br>25 mg/m <sup>3</sup> |
| TITANIUM DIOXIDE (TOTAL DUST)<br>13463-67-7     | TWA: 0.2 mg/m <sup>3</sup> nanoscale respirable particulate matter<br>TWA: 2.5 mg/m <sup>3</sup> finescale respirable particulate matter         | TWA: 15 mg/m <sup>3</sup> total dust        | 5000 mg/m <sup>3</sup>                        |
| STODDARD SOLVENT (MINERAL SPIRITS)<br>8052-41-3 | TWA: 100 ppm   | TWA: 500 ppm<br>TWA: 2900 mg/m <sup>3</sup> | 20000 mg/m <sup>3</sup>                       |

#### Appropriate engineering controls

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA

Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV).  
Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

#### **Individual protection measures, such as personal protective equipment**

|                                       |  |
|---------------------------------------|--|
| <b>Eye/face protection</b>            | Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.   |
| <b>Skin and body protection</b>       | Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.   |
| <b>Respiratory protection</b>         | Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs. |
| <b>General hygiene considerations</b> | Handle in accordance with good industrial hygiene and safety practice.<br>Avoid breathing dust created by cutting, sanding, or grinding.   |

### **9. PHYSICAL AND CHEMICAL PROPERTIES**

#### **Information on basic physical and chemical properties**

|                       |                          |                       |                          |
|-----------------------|--------------------------|-----------------------|--------------------------|
| <b>Physical state</b> | liquid                   | <b>Odor</b>           | Slight                   |
| <b>Appearance</b>     | opaque                   | <b>Odor threshold</b> | No information available |
| <b>Color</b>          | No information available |                       |                          |

| <b><u>Property</u></b>                        | <b><u>Values</u></b>     | <b><u>Remarks</u></b>    |
|---|--------------------------|--------------------------|
| <b>pH</b>                                     |                          | No data available        |
| <b>Melting point / freezing point</b>         | No data available        | No data available        |
| <b>Boiling point / boiling range</b>          | 72 °C / 162 °F           |                          |
| <b>Flash point</b>                            | No information available | No information available |
| <b>Evaporation rate</b>                       |                          | No data available        |
| <b>Flammability (solid, gas)</b>              | No data available        |                          |
| <b>Flammability Limit in Air</b>              |                          |                          |
| <b>Upper flammability limit</b>               | N/A                      |                          |
| <b>Lower flammability limit</b>               | N/A                      |                          |
| <b>Vapor pressure</b>                         |                          | No data available        |
| <b>Vapor density</b>                          |                          | No data available        |
| <b>Specific gravity</b>                       | 1.58034                  |                          |
| <b>Water solubility</b>                       | Insoluble in cold water  |                          |
| <b>Solubility in other solvents</b>           |                          | No data available        |
| <b>Partition coefficient: n-octanol/water</b> |                          | No data available        |
| <b>Autoignition temperature</b>               | No data available        | No data available        |
| <b>Decomposition temperature</b>              | No information available |                          |
| <b>Kinematic viscosity</b>                    | No information available |                          |
| <b>Dynamic viscosity</b>                      |                          | No data available        |

#### **Other Information**

|   |                          |
|---|--------------------------|
| <b>Molecular weight</b>                         | No information available |
| <b>Density</b>                                  | 13.18                    |
| <b>Volatile organic compounds (VOC) content</b> | 0.24778                  |
| <b>Total volatiles weight percent</b>           | 1.88 %                   |
| <b>Total volatiles volume percent</b>           | 3.05 %                   |
| <b>Bulk density</b>                             | No information available |

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks. Epoxy constituents.

### Incompatible materials

Strong oxidizing agents, Acids, Bases, Hypochlorites, Nitrous acid and other nitrosating agents, Peroxides

### Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Nitric acid, nitrosamine. Hydrocarbons. Carbon oxides. Aldehydes. Ammonia. Ketones. Sulfur oxides. Phenolics.

## 11. TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

|                     |   |
|---------------------|---|
| <b>Inhalation</b>   | May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs. |
| <b>Eye contact</b>  | Causes serious eye damage.  |
| <b>Skin contact</b> | Irritating to skin. May cause sensitization by skin contact.  |
| <b>Ingestion</b>    | Harmful if swallowed.   |

### Information on toxicological effects

|                 |  |
|-----------------|--|
| <b>Symptoms</b> | Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders. Skin irritation. Serious eye damage/eye irritation. |
|-----------------|--|

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

|                                  |  |
|----------------------------------|--|
| <b>Skin corrosion/irritation</b> | sensitizer. Irritating to skin.  |
| <b>Eye damage/irritation</b>     | Risk of serious damage to eyes.  |
| <b>Corrosivity</b>               | Corrosive to the eyes and may cause severe damage including blindness.   |
| <b>Chronic Toxicity</b>          | Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure). Substances known to impair fertility. Substances known to be mutagenic to man. Skin sensitizer. Causes damage to organs through prolonged or repeated exposure. |
| <b>Sensitization</b>             | May cause sensitization of susceptible persons.  |
| <b>Mutagenicity</b>              | May cause genetic defects.   |
| <b>Carcinogenicity</b>           | The table below indicates whether each agency has listed any ingredient as a carcinogen.   |

| Chemical name                             | ACGIH | IARC     | NTP   | OSHA |
|---|-------|----------|-------|------|
| CRYSTALLINE SILICA (QUARTZ)<br>14808-60-7 | A2    | Group 1  | Known | X    |
| TITANIUM DIOXIDE (TOTAL)                  | A3    | Group 2B | -     | X    |

|                     |  |  |  |  |
|---------------------|--|--|--|--|
| DUST)<br>13463-67-7 |  |  |  |  |
|---------------------|--|--|--|--|

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

#### Reproductive effects

May damage fertility or the unborn child.

#### STOT - single exposure

Causes damage to organs

#### STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure

#### Aspiration hazard

No information available.

#### Acute Toxicity

24.2484018 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

Toxic to aquatic life with long lasting effects

58.31093 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

| Chemical name              | Toxicity to algae   | Toxicity to fish  | Toxicity to daphnia                |
|----------------------------|---|---|------------------------------------|
| BENZYL ALCOHOL<br>100-51-6 | -   | LC50: 460 mg/L Pimephales promelas 96 h static<br>LC50: 10 mg/L Lepomis macrochirus 96 h static                   | EC50: 23 mg/L water flea 48 h      |
| NONYLPHENOL<br>84852-15-3  | EC50: 0.36 - 0.48 mg/L Pseudokirchneriella subcapitata 96 h static<br>EC50: 0.16 - 0.72 mg/L Pseudokirchneriella subcapitata 72 h static<br>EC50: 1.3 mg/L Desmodesmus subspicatus 72 h | LC50: 0.135 mg/L Pimephales promelas 96 h flow-through<br>LC50: 0.1351 mg/L Lepomis macrochirus 96 h flow-through | EC50: 0.14 mg/L Daphnia magna 48 h |

#### Persistence and degradability

No information available.

#### Bioaccumulation

No information available.

#### Mobility in Environmental Media

No information available

| Chemical name                                   | log Pow |
|---|---------|
| BENZYL ALCOHOL<br>100-51-6                      | 1.1     |
| POLYOXYPROPYLENETRIAMINE<br>39423-51-3          | -1.13   |
| MODIFIED CYCLOALIPHATIC POLYAMINE<br>1761-71-3  | 2.03    |
| NONYLPHENOL<br>84852-15-3                       | 5.4     |
| STODDARD SOLVENT (MINERAL SPIRITS)<br>8052-41-3 | 6.4     |

#### Other Adverse Effects

No information available

## 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

#### Disposal Methods

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

**California Hazardous Waste Status**

| Chemical name                                 | CAWAST |
|---|--------|
| SILICON DIOXIDE/ALUMINUM OXIDES<br>66402-68-4 | Toxic  |

**14. TRANSPORT INFORMATION****DOT****Proper Shipping Name  
Additional Information**

PAINT & RELATED MATERIAL NOT REGULATED

The above transport information is for non-bulk packaging only ( $\leq 119$  gallons). For additional information, contact Tnemec Traffic Department at 816-474-3400 or [traffic@tnemec.com](mailto:traffic@tnemec.com).

**IATA****UN/ID no.  
Proper Shipping Name  
Hazard Class  
Packing Group  
ERG Code**

UN3082  
Environmentally hazardous substance, liquid, n.o.s, (NONYL PHENOL)  
9  
III  
171

**IMDG/IMO****UN/ID no.  
Proper Shipping Name  
Hazard Class  
Packing Group  
EmS No.  
Marine Pollutant**

UN3082  
Environmentally hazardous substance, liquid, n.o.s, (NONYL PHENOL)  
9  
III  
F-A,S-F  
Yes

**Additional Information**

Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION****International Inventories**

|               |                 |
|---------------|-----------------|
| TSCA          | Complies        |
| DSL/NDL       | Complies        |
| EINECS/ELINCS | Does Not Comply |
| ENCS          | Does Not Comply |
| IECSC         | Complies        |
| KECL          | Does Not Comply |
| PICCS         | Does Not Comply |
| AICS          | Does Not Comply |

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances



**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

| Chemical name                   | HAPS Data |
|---------------------------------|-----------|
| SILICON DIOXIDE/ALUMINUM OXIDES |           |

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

| Chemical name                                | SARA 313 - Threshold Values |
|--|-----------------------------|
| SILICON DIOXIDE/ALUMINUM OXIDES - 66402-68-4 | 1.0                         |
| NONYLPHENOL - 84852-15-3                     | 1.0                         |

**SARA 311/312 Hazardous****Categorization**

|                                   |     |
|-----------------------------------|-----|
| Acute Health Hazard               | Yes |
| Chronic Health Hazard             | Yes |
| Fire Hazard                       | No  |
| Sudden Release of Pressure Hazard | No  |
| Reactive Hazard                   | No  |

**Clean Water Act**

| Chemical name                                 | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---|-----------------------------|------------------------|---------------------------|----------------------------|
| SILICON DIOXIDE/ALUMINUM OXIDES<br>66402-68-4 |                             | X                      |                           |                            |

**TSCA 5(a)2 Significant New Use Rule (SNUR)**

This product contains one or more substances which are subject to a TSCA Section 5 Significant New Use Rule (SNUR).

| Chemical name | TSCA 5(a)2                             |
|---------------|--|
| NONYLPHENOL   | 79 FR 59186, Oct 1, 2014 proposed rule |

**California Prop. 65**

**WARNING:** This product can expose you to the following chemicals which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

| Chemical name                              | California Prop. 65 |
|--|---------------------|
| CRYSTALLINE SILICA (QUARTZ) - 14808-60-7   | Carcinogen          |
| TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7 | Carcinogen          |
| AMORPHOUS SILICA - 7631-86-9               | Carcinogen          |
| CARBON BLACK DUST & FUME - 1333-86-4       | Carcinogen          |

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

| Chemical name                                 | New Jersey | Massachusetts | Pennsylvania |
|---|------------|---------------|--------------|
| CRYSTALLINE SILICA (QUARTZ)<br>14808-60-7     | X          | X             | X            |
| BENZYL ALCOHOL<br>100-51-6                    |            | X             | X            |
| SILICON DIOXIDE/ALUMINUM OXIDES<br>66402-68-4 | X          |               | X            |
| TITANIUM DIOXIDE (TOTAL DUST)<br>13463-67-7   | X          | X             | X            |
| STODDARD SOLVENT (MINERAL)                    | X          | X             | X            |

|                       |  |  |  |
|-----------------------|--|--|--|
| SPIRITS)<br>8052-41-3 |  |  |  |
|-----------------------|--|--|--|

**16. OTHER INFORMATION**

|   |           |                |               |                   |
|---|-----------|----------------|---------------|-------------------|
| <b>NFPA</b>   | Health 3  | Flammability 0 | Instability 1 | Physical hazard * |
| <b>HMIS (Hazardous<br/>Material Information<br/>System)</b> | Health 3* | Flammability 0 | Reactivity 1  |                   |


|                              |                                      |
|------------------------------|--------------------------------------|
| <b>Prepared By</b>           | Tnemec Regulatory Dept: 816-474-3400 |
| <b>Issue Date</b>            | 19-May-2017                          |
| <b>Revision Date</b>         | 30-Jan-2024                          |
| <b>Revision Summary</b>      |                                      |
| 9 4 2 5 7 10 8 11 14 1 13 15 |                                      |

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**



# Safety Data Sheet

Issue Date 30-Jan-2024

Revision Date 30-Jan-2024

Revision Number 14

## 1. IDENTIFICATION

### Product identifier

Product Code S282-0282B  
Product Name TNEME-GLAZE CONVERTER

### Other means of identification

Common Name SERIES 282, PART B  
Synonyms None

### Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.  
Uses advised against Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 123 W. 23rd Avenue, North Kansas City, MO 64116-3094 (816) 474-3400

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400  
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

|  |             |
|--|-------------|
| Skin corrosion/irritation                          | Category 2  |
| Serious eye damage/eye irritation                  | Category 2  |
| Germ cell mutagenicity                             | Category 1B |
| Carcinogenicity                                    | Category 1B |
| Reproductive Toxicity                              | Category 2  |
| Specific target organ toxicity (repeated exposure) | Category 1  |

### Label elements

## EMERGENCY OVERVIEW

### **Danger**

#### **Hazard statements**

Causes skin irritation  
Causes serious eye irritation  
May cause genetic defects  
May cause cancer  
Suspected of damaging fertility or the unborn child  
Causes damage to organs through prolonged or repeated exposure

**Appearance** clear**Physical state** liquid**Odor** Slight**Precautionary Statements****Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Do not breathe dust/fume/gas/mist/vapors/spray  
Do not eat, drink or smoke when using this product

**Response**

IF exposed or concerned: Get medical advice/attention  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
IF ON SKIN: Wash with plenty of soap and water  
If skin irritation occurs: Get medical advice/attention  
Take off contaminated clothing and wash before reuse

**Storage**

Store locked up  
Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

May be harmful in contact with skin  
Toxic to aquatic life with long lasting effects  
SEE SAFETY DATA SHEET

Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

| Chemical name              | CAS No.    | Weight-%  |
|----------------------------|------------|-----------|
| EPOXY RESIN                | 28064-14-4 | 60 - 100% |
| BENZYL ALCOHOL             | 100-51-6   | 1 - <10%  |
| NONYLPHENOL                | 84852-15-3 | 1 - <10%  |
| PETROLEUM SOLVENT (NAPTHA) | 64742-95-6 | 0.1 - <1% |

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES****Description of first aid measures****General advice**

If symptoms persist, call a physician.

|   |  |
|---|--|
| <b>Eye contact</b>                        | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.   |
| <b>Skin contact</b>                       | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician. |
| <b>Inhalation</b>                         | Remove to fresh air. Oxygen or artificial respiration if needed.   |
| <b>Ingestion</b>                          | If swallowed, do not induce vomiting. Get medical attention immediately.   |
| <b>Self-protection of the first aider</b> | Use personal protective equipment. Avoid contact with eyes, skin and clothing.   |

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Nitrogen oxides (NOx). Aldehydes. Ammonia. Ketones. Nitric acid, nitrosamine. Phenolics. Silicon.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents. Water. Acids. Nitrous acid and other nitrosating agents. Peroxides. Amines.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

#### Appropriate engineering controls

**Engineering measures** Ensure adequate ventilation, especially in confined areas.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

|                       |           |                       |                          |
|-----------------------|-----------|-----------------------|--------------------------|
| <b>Physical state</b> | liquid    | <b>Odor</b>           | Slight                   |
| <b>Appearance</b>     | clear     | <b>Odor threshold</b> | No information available |
| <b>Color</b>          | Colorless |                       |                          |

| <u>Property</u>                | <u>Values</u>            | <u>Remarks</u> |
|--------------------------------|--------------------------|----------------|
| pH                             |                          |                |
| Melting point / freezing point | No data available        |                |
| Boiling point / boiling range  |                          |                |
| Flash point                    | No information available |                |
| Evaporation rate               |                          |                |
| Flammability (solid, gas)      | No data available        |                |

|   |                          |       |  |  |
|---|--------------------------|-------|--|--|
| <b>Flammability Limit in Air</b>              |                          |       |  |  |
| Upper flammability limit                      | N/A                      |       |  |  |
| Lower flammability limit                      | N/A                      |       |  |  |
| <b>Vapor pressure</b>                         |                          |       |  |  |
| <b>Vapor density</b>                          |                          |       |  |  |
| Specific gravity                              | 1.18704                  | g/cm3 |  |  |
| Water solubility                              | Insoluble in cold water  |       |  |  |
| <b>Solubility in other solvents</b>           |                          |       |  |  |
| <b>Partition coefficient: n-octanol/water</b> |                          |       |  |  |
| Autoignition temperature                      | No data available        |       |  |  |
| Decomposition temperature                     | No information available |       |  |  |
| Kinematic viscosity                           | No information available |       |  |  |
| Dynamic viscosity                             | 9120 centipoises         |       |  |  |

**Other Information**

|  |                          |
|--|--------------------------|
| Molecular weight                         | No information available |
| Density                                  | 9.89993 lbs/gal          |
| Volatile organic compounds (VOC) content | 0.03861 lbs/gal          |
| Total volatiles weight percent           | 0.39 %                   |
| Total volatiles volume percent           | 0.52 %                   |
| Bulk density                             | No information available |

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks. Contact with water or moist air liberates irritating gas (methanol).

**Incompatible materials**

Strong oxidizing agents, Water, Acids, Nitrous acid and other nitrosating agents, Peroxides, Amines

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Nitrogen oxides (NOx). Hydrocarbons. Aldehydes. Ammonia. Ketones. Nitric acid, nitrosamine. Phenolics. Silicon.

**11. TOXICOLOGICAL INFORMATION****Information on Likely Routes of Exposure**

|                     |   |
|---------------------|---|
| <b>Inhalation</b>   | May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. |
| <b>Eye contact</b>  | Severely irritating to eyes.  |
| <b>Skin contact</b> | Irritating to skin. May cause sensitization of susceptible persons.   |
| <b>Ingestion</b>    | Harmful if swallowed.   |

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Skin corrosion/irritation** Irritating to skin. sensitizer.  
**Eye damage/irritation** Causes serious eye irritation.  
**Chronic Toxicity** Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause cancer. May cause genetic defects. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.  
**Sensitization** May cause sensitization of susceptible persons.  
**Mutagenicity** Not classified.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.  
**Reproductive effects** Not classified.  
**STOT - single exposure** No information available  
**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure  
**Aspiration hazard** No information available.

**Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity.

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Toxic to aquatic life with long lasting effects

0.01825636 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

| Chemical name                            | Toxicity to algae   | Toxicity to fish  | Toxicity to daphnia                |
|--|---|---|------------------------------------|
| BENZYL ALCOHOL<br>100-51-6               | -   | LC50: 460 mg/L Pimephales promelas 96 h static<br>LC50: 10 mg/L Lepomis macrochirus 96 h static                   | EC50: 23 mg/L water flea 48 h      |
| NONYLPHENOL<br>84852-15-3                | EC50: 0.36 - 0.48 mg/L Pseudokirchneriella subcapitata 96 h static<br>EC50: 0.16 - 0.72 mg/L Pseudokirchneriella subcapitata 72 h static<br>EC50: 1.3 mg/L Desmodesmus subspicatus 72 h | LC50: 0.135 mg/L Pimephales promelas 96 h flow-through<br>LC50: 0.1351 mg/L Lepomis macrochirus 96 h flow-through | EC50: 0.14 mg/L Daphnia magna 48 h |
| PETROLEUM SOLVENT (NAPTHA)<br>64742-95-6 | -   | LC50: 9.22 mg/L Oncorhynchus mykiss 96 h  | EC50: 6.14 mg/L Daphnia magna 48 h |

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

| Chemical name              | log Pow |
|----------------------------|---------|
| BENZYL ALCOHOL<br>100-51-6 | 1.1     |
| NONYLPHENOL<br>84852-15-3  | 5.4     |

**Other Adverse Effects** No information available



### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

##### Disposal Methods

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

##### Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

##### US EPA Waste Number

| Chemical name             | RCRA | RCRA - Basis for Listing  | RCRA - D Series Wastes | RCRA - U Series Wastes |
|---------------------------|------|---|------------------------|------------------------|
| PHENOL (SKIN)<br>108-95-2 | U188 | Included in waste streams:<br>F039, K001, K022, K087<br>Included in waste stream:<br>K060 |                        | U188                   |
| METHYL ALCOHOL            |      | Included in waste stream:<br>F039   |                        | U154                   |

### 14. TRANSPORT INFORMATION

#### DOT

##### Proper Shipping Name Additional Information

PAINT & RELATED MATERIAL NOT REGULATED

The above transport information is for non-bulk packaging only ( $\leq 119$  gallons). For additional information, contact Tnemec Traffic Department at 816-474-3400 or [traffic@tnemec.com](mailto:traffic@tnemec.com).

#### IATA

##### UN/ID no. Proper Shipping Name Hazard Class Packing Group ERG Code

UN3082  
Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin)  
9  
III  
171

#### IMDG/IMO

##### UN/ID no. Proper Shipping Name Hazard Class Packing Group EmS No. Marine Pollutant

UN3082  
Environmentally hazardous substance, liquid, n.o.s. (BENZENEMETHANOL)  
9  
III  
F-A,S-F  
Yes

#### Additional Information

Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

### 15. REGULATORY INFORMATION

#### International Inventories

|               |                 |
|---------------|-----------------|
| TSCA          | Complies        |
| DSL/NDSL      | Complies        |
| EINECS/ELINCS | Complies        |
| ENCS          | Does Not Comply |
| IECSC         | Complies        |
| KECL          | Complies        |
| PICCS         | Does Not Comply |

AICS

Does Not Comply

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

| Chemical name            | SARA 313 - Threshold Values |
|--------------------------|-----------------------------|
| NONYLPHENOL - 84852-15-3 | 1.0                         |

**SARA 311/312 Hazardous****Categorization**

|                                   |     |
|-----------------------------------|-----|
| Acute Health Hazard               | Yes |
| Chronic Health Hazard             | Yes |
| Fire Hazard                       | No  |
| Sudden Release of Pressure Hazard | No  |
| Reactive Hazard                   | No  |

**TSCA 5(a)2 Significant New Use Rule (SNUR)**

This product contains one or more substances which are subject to a TSCA Section 5 Significant New Use Rule (SNUR).

| Chemical name              | TSCA 5(a)2                             |
|----------------------------|--|
| NONYLPHENOL                | 79 FR 59186, Oct 1, 2014 proposed rule |
| PHENOL, 2-NONYL-, BRANCHED | 79 FR 59186, Oct 1, 2014 proposed rule |

**California Prop. 65**

**WARNING:** This product can expose you to the following chemicals which are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

| Chemical name    | California Prop. 65 |
|------------------|---------------------|
| METHYL ALCOHOL - | Developmental       |

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

| Chemical name              | New Jersey | Massachusetts | Pennsylvania |
|----------------------------|------------|---------------|--------------|
| BENZYL ALCOHOL<br>100-51-6 |            | X             | X            |

**16. OTHER INFORMATION****NFPA**

Health 3

Flammability 0

Instability 1

Physical hazard \*

**HMIS (Hazardous  
Material Information)**

System) Health 3\* Flammability 0 Reactivity 1

Prepared By Tnemec Regulatory Dept: 816-474-3400

Issue Date 22-May-2017

Revision Date 30-Jan-2024

Revision Summary

9 4 5 7 10 8 11 14 13

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS